



# SALES FACT SHEET

## Equipped with the Award Winning *Comfort Control System™*

- Increased Reliability
- On-Board Diagnostics
- Fault Recall
- Active Protection™



**R-410A**  
Earth Friendly Refrigerant

### UAPL- JEZ

14 SEER Models  
Efficiencies up to 16.00 SEER  
Nominal Sizes 1 1/2 to 5 Tons  
[5.28 kW] to [17.6 kW]  
**Seven Models**  
Cooling Capacities  
18,200 to 59,500 BTU/HR  
[5.33 kW] to [17.44 kW]

### UANL- JEZ

13 SEER Models  
Nominal Sizes 2 to 5 Tons  
[7.03 kW] to [17.6 kW]  
**Six Models**  
Cooling Capacities  
23,200 to 62,000 BTU/HR  
[6.80 kW] to [18.17 kW]

## GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Compressor ..... Ten (10) Years  
\*Any Other Part ..... Ten (10) Years

### UAPL- JEZ/UANL- JEZ Series Conditional Replacement Warranty:

Ruud will provide a replacement model (if an exact replacement is not available, an equivalent product will be provided) to the original purchaser if the compressor fails within 5 years (providing the unit is installed with a new Ruud Air Handler OR Ruud Indoor Coil with a Ruud Gas Furnace, and is properly matched as specified by Ruud and/or listed in the Air Conditioning Institute (ARI) published rating, and if additional conditions are satisfied. See product warranty card for additional information.

\*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.




# RUUD ULTRA<sup>®</sup> Series

## Features

The Ruud *Ultra® Series* UAPL- JEZ and UANL- JEZ Condensing Units were designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- The *Comfort Control System™* provides on-board diagnostics and fault history for condensing units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with *Active Protection* prevents compressor operation when potentially harmful conditions are detected.
- 7-Segment LED Display is exclusive only to Ruud products. The information-display quickly and accurately shows technicians the source of malfunctions.
- Five-year conditional unit replacement warranty.
- Compressor sound blanket is standard to provide quiet operation.
- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

| <u>U</u> | <u>A</u>                     | <u>P</u>                   | <u>L</u>                           | <u>—</u> | <u>018</u>                                                                                                                                                                                                                                                                             | <u>J</u>                                           | <u>E</u>                                                                  | <u>Z</u>                                                |
|----------|------------------------------|----------------------------|------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------------------------|---------------------------------------------------------|
| RUUD     | REMOTE<br>CONDENSING<br>UNIT | P = 14 SEER<br>N = 13 SEER | DESIGN<br>SERIES<br><br>L = R-410A |          | COOLING<br>CAPACITY<br><br>018 = 18,000 BTU/HR [5.28 kW]<br>024 = 24,000 BTU/HR [7.03 kW]<br>030, 031 = 30,000 BTU/HR [8.79 kW]<br>036, 037 = 36,000 BTU/HR [10.55 kW]<br>042, 043 = 42,000 BTU/HR [12.31 kW]<br>048, 049 = 48,000 BTU/HR [14.07 kW]<br>060 = 60,000 BTU/HR [17.58 kW] | ELECTRICAL<br>DESIGNATION<br><br>J = 208/230V-1-60 | VARIATIONS<br>EQUIPPED WITH<br>THE <i>COMFORT<br/>CONTROL<br/>SYSTEM™</i> | COOLING CONNECTION<br>FITTING<br><br>Z = SWEAT W/SCROLL |
| Price    |                              |                            |                                    |          |                                                                                                                                                                                                                                                                                        | Starting at:<br>\$                                 |                                                                           |                                                         |



"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your Contractor for details or visit [www.energystar.gov](http://www.energystar.gov) <<http://www.energystar.gov/>>."